evo – LRM evo – LRM evo – LRM evo – LRM evo – LRM evo – LRM evo – LRM evo – LRM evo – LRM evo – LRM evo – LRM evo LRM evo – LRM evo – LRM evo – LRM evo – LRM evo – LRM evo – LRM evo - LRM

RADIO FREQUENCY IDENTIFICATION LONG RANGE MOBILE SOLUTION

evo – LRM

Long Range Mobile RFID Reader/Writer

Features

- **Easy system integration**
- **Multiple tag reading**
- **ISO 15693 – 2 compliant contact less interface**
- **Built-in 256Kbyte FRAM or able to store approximately 5000 items**
- **Optional Ethernet connectivity**
- **Optional Bluetooth™ connectivity**

Typical Applications

- **Stock take**
- **Inventory control**
- **Library**
- **Logistics**
- **Vehicle tracking**
- **Retail**

General Specifications

Support	13.56 MHz ISO15693 standard tags
Power	DC ± 15V
Dimension	Antennas: 255mm X 255mm or 600mm X 800mm
Interface	RS232, optional Bluetooth ™, optional Ethernet
Transmission Speed	9600, n, 8, 1 up to 115.2K bps
Reading Distance	Up to 650mm depending on tag size

RF iDent continually improves products as new technologies & components become available; therefore, reserves the right to change specifications without prior notice

Website: www.rf-ident.com

Authorized distributor / reseller

evo – LRM evo – LRM evo – LRM evo – LRM evo – LRM evo – LRM evo – LRM evo – LRM evo – LRM evo – LRM evo – LRM evo LRM